

G44-HDMI

Video Wall Controller



Features

- Four HDMI 2.0 with embedded audio
- Four HDMI 2.0 with embedded audio
- Each input and output support resolutions up to 4K@60Hz 4:4:4
- Four analog audio inputs
- Four analog audio outputs
- Four digital audio outputs
- Independent 8x8 IR Matrix
- Support audio embedded and de-embedded
- Support video wall function
- Support presentation switching function
- Support seamless matrix switching function
- Support CEC management
- Support EDID management
- Custom pre-set layouts for both Matrix and Video Wall Modes
- HDCP compliant
- Customizable OSD
- Exporting and Importing OSD Settings
- Adjust Display settings such as Contrast and Saturation remotely
- Controllable via IP/serial port
- Controllable via front panel buttons
- Adjust the position of the screen remotely

Overview

The G44 HDMI version of video wall controller accepts up to 4 HDMI inputs and displays them on 4 different displays, each with a resolution up to 4K@60fps 4:4:4. G44 not only allows the user to display a single input across all four screens, but also to display different input videos onto different screens working like a matrix switcher.

In addition to the video wall and matrix switching capabilities, the G44 can act as a presentation switcher as well – enabling the user to assign audio from any of the 4 embedded digital audio inputs or 4 analog audio inputs to any of the outputs. This makes the G44 a great solution not only for digital signage, broadcasting and security, but also for meeting and conference room.

The G44 Controller can be easily configured via IP/serial port connection to a Windows based PC, running the management software, from the front panel of the unit, or through 3rd party controllers. The Windows based software provides a user-friendly GUI, greatly simplifying the system configuration. G44 controllers can run standalone without the connection to the control PC, once configured.

Specifications

| | |
|--------------------------------|-------------------------------------|
| Dimensions(W*D*H) (mm) | 480mm x 245mm x 44.55mm 1U |
| Input Resolution | Up to 3840 x 2160@60fps 4:4:4 |
| Input Format | HDMI2.0 |
| Output Resolution | Up to 3840 x 2160@60fps 4:4:4 |
| Output Format | HDMI2.0 |
| IR Port | 3.5mm Jack |
| Analog Audio Output Interface | 5-way Phoenix connectors |
| Digital Audio Output Interface | Mini Toslink jackets |
| Analog Audio Input Interface | 3-way Phoenix connectors |
| HDCP | Yes |
| Power Supply | 110-240VAC |
| Video Wall Capabilities | Yes |
| Remotely Fine Tune Settings | Yes |
| Operating Temperature Range | 0~40 degrees centigrade |
| Operating Humidity Range | 10%-90% non-condensing |
| Storage Temperature Range | -20~60 degrees centigrade |
| Storage Humidity Range | 10%~90% non-condensing |
| Control Interface | 10/100/1000M Ethernet Port or RS232 |
| Max Power Consumption | 60W |
| Warranty | 2 years |

Models

| Models | Input | | Output | |
|----------|-----------|----------|-----------|----------|
| | Connector | Format | Connector | Format |
| G44-HDMI | HDMI A | HDMI 2.0 | HDMI A | HDMI 2.0 |

System Diagram

