

SEADA CONFERENCE Motorised & Retractable Tablet



This system can be used as a standalone unit in class rooms, offices, receptions etc. It can be used not only as a tablet but also a PC. In addition it can operate as a multi units' system with the SEADA paperless conference platform. SEADA conference platform has multiple screens across the table which allows all the participants to have a clear view of the information.

When it is not in use, the tablet can be retracted into the housing beneath the desk. This makes the desk surface tidy as well as putting the tablet in a safe and secure location.

- Ergonomic design
- Optimised viewing angle
- > Adjustable viewer angle
- HDCP compliance
- Detachable Tablet
- Secure
- Auto switching between wireless and Ethernet connection
- Compatible with SEADA Multimedia
 Conference Platform

SEADA CONFERENCE

Oak Tree Park Burnt Meadow Road Moons Moat North Industrial Estate, Redditch, Worcestershire, UK, B98 9NW www.seada.co.uk Email: sales@seada.co.uk Phone: +44 (0)1527 584364 Fax: +44 (0)1527 962998

Solutions that work for your meeting and conference room.

MOTORISED & RETRACTABLE TABLET

From SEADA CONFERENCE

Specifications

Model	SC13FP
Operating System	Windows 10 Pro
Screen Type	IPS LCD
Brightness	250cd/m ²
Touch Enabled	Yes
Tablet Output Port	HDMI mini 1.4
Tablet Input Ports	USB3.0x2, Microphone port
Base Ports	USB3.0x2, DC IN, Ethernet
Wireless	802.11ac/a/b/g/n, 2.4G + 5G
Screen Size (inches)	13.3
Display Resolution	1920x1080
Processor	Intel i3-8130U
System Memory (RAM)	DDR4 4GB
Graphics Card	Intel UHF Graphics 620@1.10GHz
Hard Drive	SSD 64GB
Bluetooth	BT 4.2
Built in Web Cam	Yes

Viewing Angle	0-25°
Control	RS485 & remote control
Wireless/Ethernet Auto Switch	Yes
Detachable Tablet	Yes
Frame Finish	Anodised Aluminium
System Desktop Frame Size	383mm*75mm*3mm
Housing Desktop Cut Size	376mm* 69mm
System Weight	9.5kg
System Dimensions	383mm*75mm*475mm
System Shipping Weight	10kg
System Shipping Dimensions	700mm*200mm*600mm
Operating Temperature Range	0~40°
Operating Humidity Range	10%~90% non-condensing
Storage Temperature Range	-20~60°
Storage Temperature Range	10%~90% non-condensing
Parts Warranty	3 Years

