

SD-DCSRB

Wired Microphone Host Units



Overview

The SD-DCSRB microphone host unit is a high-quality call station with a sturdy metal base designed for use with the SD-DCSR digital conference system. The SD-DCSRB microphone units can be connected in a daisy-chain configuration with up to 100 units to one SD-DCSR digital conference system. The 4-pin CB connector allows the convenient installation of different brands of microphones.

The SD-DCSRB also features with multiple buttons for incorporating with the control unit, including speak ON/OFF, volume adjustment and so on. With the on-unit display, user is also able to view information including unit status and timing on the microphone unit. The chairman unit comes with a priority chairman key, which can take over delegate units.

SD-DCSRB is a perfect microphone unit giving participants a chance to take part in a discussion by speaking into the microphone, working along with the control unit in different scenarios such as large conferencing rooms.

Key Feature

- High grade and modern aesthetic design
- Powered by the system host
- Stand 4-pin CB connector for easy installation and swap
- RJ45 for point-to-point connection and power
- Anti-interference circuit design to prevent interference from electronic products such as mobile phones
- One-button click for speech
- Multi-button for operation of the unit
- On-unit display for unit status and timing
- Priority chairman key

Specifications

SD-DCSRB-C Chairman Unit	
Power Supply	DC 24V
Working Current	60mA
Connector	RJ45 x1; 3.5mm x1
Weight	0.95kg
Dimension	146x124x46 mm
Colour	Black
Button	Priority Key x1, Mic ON/OFF Key x1 Volume Up x1, Volume Down x1
SD-DCSRB-D Delegate Unit	
Power Supply	DC 24V
Working Current	60mA
Connector	RJ45 x1; 3.5mm x1
Weight	0.95kg
Dimension	146x124x46 mm
Colour	Black
Button	Mic ON/OFF Key x1, Volume Up x1, Volume Down x1

System Diagram

